


Model **CE-600S**

Operating range Arm length 600mm Joint#3 stroke 40mm

Payload Rated 5kg/Maximum 10kg

Standard cycle time 0.6 sec



Cycle time based on round-trip arch motion (300mm horizontal,25mm vertical) with 2kg payload (path coordinates optimized for maximum speed)

Repeatability  $\pm 0.02\text{mm}$   $\pm 0.02\text{mm}$   $\pm 0.01^\circ$   
Joint #1,#2 Joint #3 Joint #4

Parameters of each axis

Joint Content	#1\#5	#2	#3	#4
MAX Operating Speed	7033mm/s	3082mm/s	2346mm/s	3625°/s
MAX Motion Range	$\pm 225^\circ$	$\pm 225^\circ$	40mm	$\pm 360^\circ$
Motor Power Consumption	1000W	750W	100W	100W
Joint#3 down force	-	-	-	-
Weight	47kg (cables not included)			

Joint #4 allowable moment of inertia, rate 0.005kg·m<sup>2</sup>, maximum 0.05kg·m<sup>2</sup>

Electrical parameters	Origin Return	None Need Origin Return
Installed wire for customer	26+16 Pin (Max),with Six Working header(21)	
Installed pneumatic tube for customer use	$\phi 6\text{mm} \times 2$	
Visual Interface	2	
Installation Environment	Standerd/Clean (Customized)	

Outer Dimensions and Motion Range

